

TROLLEY BOOSTER 211

Elevation change	Overall Length Horizontal	H.P.	Shipping Weight lbs	Price
2'-0"	14'-9"	1/3	500	
3'-0"	16'-6"	1/3	525	
4'-0"	18'-0"	1/3	550	
5'-0"	20'-0"	1/3	575	
6'-0"	21'-9"	1/2	600	
7'-0"	23'-5"	1/2	625	
8'-0"	25'-4"	1/2	650	
9'-0"	26'-11"	1/2	675	
10'-0"	28'-8"	1/2	700	
11'-0"	30'-5"	3/4	725	
12'-0"	32'-1"	3/4	750	
13'-0"	33'-10"	3/4	775	
14'-0"	35'-7"	3/4	800	
15'-0"	37'-4"	3/4	825	
16'-0"	39'-1"	3/4	850	

Additional length to Upper or Lower Horizontal, add per ft. \$

STANDARD EQUIPMENT

Motor 115 / 2-8 / 220 volt; 1 or 3 phase
Adjustable torque limiter
Bi-directional pivoting pushers every 8'
Adjustable take-up and rail supports
Trolley rail to match 1-1/16" or 1-5/16"
Incline guard rail

OPTIONAL EQUIPMENT

Electrical control package including push button stations, UP/Down/Stop, reversing contactor, low voltage control transformer, pre-wired ready for supply connection.

<u>Line</u>	<u>Controls</u>
18211-1151-	155V, 1 phase24V\$
18211-2201 –	208/230V, 1 phase..24V\$
18211-2203 –	208/230V, 3 phase ..24V\$
211 IOTS -	Incline other than 30 degrees ...\$
212 -24 -	full line sensor 24V \$
212 – 115 –	full line sensor 115V \$